

according to UK REACH Regulation

PREMA DEMONTAGE FLUID

Revision date: 21.01.2021 Product code: 00623-0032 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PREMA DEMONTAGE FLUID

Art.-No.

PDF-5 (SKU No. 2201050)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Tire demounting agent

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: PREMA GmbH
Street: Aspertsham 40
Place: D-94081 Fürstenzell
Telephone: +49 (0) 8502 917 150 0

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

Company name: Harvie Tyres Ltd.

Street: Units 7 & 8 Apollo Court Hallam Way

Place: Whitehills Business Park Blackpool Lancashire, FY4 5FS

Telephone: +44 (0) 1253 741790 Internet: www.harvie.co.uk

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories:

Respiratory or skin sensitisation: Skin Sens. 1A

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

octhilinone (ISO); 2-octyl-2H-isothiazol-3-one

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.



Print date: 02.09.2021



according to UK REACH Regulation

PREMA DEMONTAGE FLUID

Revision date: 21.01.2021 Product code: 00623-0032 Page 2 of 9

Precautionary statements

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P273 Avoid release to the environment.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Aqueous solution

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
52-51-7	bronopol (INN); 2-bromo-2-nitropropane-1,3-diol		< 0,1 %	
	200-143-0	603-085-00-8	01-2119980938-15	
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 2; H312 H302 H315 H318 H335 H400 H411			
26530-20-1	octhilinone (ISO); 2-octyl-2H-isothiazol-3-one		< 0,1 %	
	247-761-7	613-112-00-5	01-2120768921-45	
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1A, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

If you feel unwell, seek medical advice.

After inhalation

Move to fresh air in case of accidental inhalation of fumes from overheating or combustion.

After contact with skin

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse thoroughly with plenty of water, also under the eyelids.

If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Consult a physician.

Induce vomiting only upon the advice of a physician.



Print date: 02.09.2021



according to UK REACH Regulation

PREMA DEMONTAGE FLUID

Revision date: 21.01.2021 Product code: 00623-0032 Page 3 of 9

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Repeated or prolonged exposure may cause irritation of eyes and skin.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Traces of

nitrogen gases (NOx)

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Wash hands before breaks and at the end of workday.

Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.



Print date: 02 09 2021



according to UK REACH Regulation

PREMA DEMONTAGE FLUID

Revision date: 21.01.2021 Product code: 00623-0032 Page 4 of 9

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Tire demounting agent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

This product does not contain any substances for which a Workplace Exposure Limit has been set in concentrations above the limits.

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Wash hands before breaks and at the end of workday.

When using do not eat or drink.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Safety goggles (EN 166).

Hand protection

Protective gloves resistant to chemicals made off natural-rubber latex, minimum coat thickness 0.6 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Lapren 706> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

Not required; except in case of aerosol formation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: Greenish-blue

Odour: Mild

	Test ı
pH-Value:	7,4
Changes in the physical state	
Melting point/freezing point:	n.d.
Boiling point or initial boiling point and boiling range:	n.d.
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	n.a.

Revision No: 1,2 - Replaces version: 1,1 GB - EN Print date: 02.09.2021



method



according to UK REACH Regulation

PREM	пΛ	DEM		$T \wedge C$	2		חו
PREIV	ΙА	DEIV	IUI	IAU	3 E I	FLU	ıv

Revision date: 21.01.2021 Product code: 00623-0032 Page 5 of 9

Sustaining combustion: Not sustaining combustion

Flammability

Solid: n.a. Gas: n.a.

Explosive properties

The product is not explosive.

Lower explosion limits:

Upper explosion limits:

n.a.

Auto-ignition temperature:

n.a.

Self-ignition temperature

Solid: n.a. Gas: n.a.
Decomposition temperature: n.d.

Oxidizing properties

Not oxidising.

Vapour pressure: 24 hPa

(at 20 °C)

Density (at 20 °C): 1,06 g/cm³
Bulk density: n.a.
Water solubility: Completely miscible

(at 15 °C)

Solubility in other solvents

n.d.

Partition coefficient n-octanol/water:

Viscosity / dynamic:

n.d.

Viscosity / kinematic:

n.d.

Flow time: 15 s 4 DIN/ISO 2431

(at 20 °C)

Relative vapour density:

Evaporation rate:

n.d.

Solvent separation test:

0 %

Solvent content:

0 %

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

10.4. Conditions to avoid

No data available





according to UK REACH Regulation

PREMA DEMONTAGE FLUID

Revision date: 21.01.2021 Product code: 00623-0032 Page 6 of 9

10.5. Incompatible materials

No incompatible products to be specially mentioned.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (octhilinone (ISO); 2-octyl-2H-isothiazol-3-one)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Repeated or prolonged exposure may cause irritation of eyes and skin.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Further information

Product is not allowed to be discharged into aquatic environment.

SECTION 13: Disposal considerations



Print date: 02 09 2021



according to UK REACH Regulation

PREMA DEMONTAGE FLUID

Revision date: 21.01.2021 Product code: 00623-0032 Page 7 of 9

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

070699 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; wastes not otherwise specified

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information



Print date: 02 09 2021



according to UK REACH Regulation

PREMA DEMONTAGE FLUID

Revision date: 21.01.2021 Product code: 00623-0032 Page 8 of 9

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC):

Information according to 2012/18/EU

(SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

> work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intér IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H301	l oxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns a

and eye damage.

Causes skin irritation. H315

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H330 Fatal if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.



Print date: 02.09.2021



according to UK REACH Regulation

PREMA DEMONTAGE FLUID

Revision date: 21.01.2021 Product code: 00623-0032 Page 9 of 9

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

