

according to UK REACH Regulation

# **Prema Adhesive Weight Remover**

Revision date: 01.09.2021 Product code: 00623-0017 Page 1 of 12

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Prema Adhesive Weight Remover

Art.-No.

PAWR-1 (SKU No. 220 3010), PAWR-500 (SKU No. 2203020)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Cleaning agent

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: PREMA GmbH
Street: Aspertsham 40
Place: D-94081 Fürstenzell
Telephone: +49 (0) 8502 917 150 0

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

**Supplier** 

Company name: Harvie Tyres Ltd.

Street: Units 7 & 8 Apollo Court Hallam Way

Place: Whitehills Business Park Blackpool Lancashire, FY4 5FS

Telephone: +44 (0) 1253 741790 Internet: www.harvie.co.uk

**1.4. Emergency telephone** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

# **GB CLP Regulation**

Hazard categories: Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

#### **GB CLP Regulation**

# Hazard components for labelling

Ethyl acetate

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

Hydrocarbons, C6, isoalkanes, < 3% n-hexane

Signal word: Danger

Print date: 01.09.2021



# **Safety Data Sheet**

according to UK REACH Regulation

# **Prema Adhesive Weight Remover**

Revision date: 01.09.2021 Product code: 00623-0017 Page 2 of 12

## Pictograms:







#### **Hazard statements**

| H222 | Extremely flammable aerosol.                     |
|------|--|
| H229 | Pressurised container: May burst if heated.      |
| H319 | Causes serious eye irritation.                   |
| H315 | Causes skin irritation.                          |
| H336 | May cause drowsiness or dizziness.               |
| H411 | Toxic to aquatic life with long lasting effects. |

## **Precautionary statements**

| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No |
|------|---|
|      | amaking   |

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Heating will cause pressure rise with risk of bursting.

# **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

## **Chemical characterization**

Preparation with aliphatic hydrocarbons (free of aromatic hydrocarbons)



according to UK REACH Regulation

# **Prema Adhesive Weight Remover**

Revision date: 01.09.2021 Product code: 00623-0017 Page 3 of 12

# **Hazardous components**

| CAS No     | Chemical name   |  |                                 | Quantity   |
|------------|---|--|---------------------------------|------------|
|            | EC No   | Index No                                   | REACH No                        |            |
|            | GHS Classification  | •  |                                 |            |
| 141-78-6   | Ethyl acetate   |  |                                 | 25 - 50 %  |
|            | 205-500-4   | 607-022-00-5                               | 01-2119475103-46                |            |
|            | Flam. Liq. 2, Eye Irrit. 2, STO                               | T SE 3; H225 H319 H336 EUH066              |                                 |            |
| 64742-49-0 | Hydrocarbons, C7, n-alkanes                                   | isoalkanes, cycloalkanes                   |                                 | 10 - 25 %  |
|            | 927-510-4   |  | 01-2119475515-33                |            |
|            | Flam. Liq. 2, Skin Irrit. 2, STC<br>H411                      | T SE 3, Asp. Tox. 1, Aquatic Chro          | nic 2; H225 H315 H336 H304      |            |
| 106-97-8   | Butane  |  |                                 | 10 - 25 %  |
|            | 203-448-7   | 601-004-00-0                               | 01-2119474691-32                |            |
|            | Flam. Gas 1, Compressed ga                                    | s; H220 H280                               |                                 |            |
| 74-98-6    | Propane   |  |                                 | 10 - 25 %  |
|            | 200-827-9   | 601-003-00-5                               | 01-2119486944-21                |            |
|            | Flam. Gas 1, Compressed ga                                    | s; H220 H280                               |                                 |            |
| 64742-49-0 | Hydrocarbons, C6, isoalkanes                                  | s, < 3% n-hexane                           |                                 | 10 - 25 %  |
|            | 931-254-9   |  | 01-2119484651-34                |            |
|            | Flam. Liq. 2, Skin Irrit. 2, STC<br>H411                      | T SE 3, Asp. Tox. 1, Aquatic Chro          | nic 2; H225 H315 H336 H304      |            |
| 75-28-5    | Isobutane   |  |                                 | 2,5 - 10 % |
|            | 200-857-2   | 601-004-00-0                               | 01-2119485395-27                |            |
|            | Flam. Gas 1, Compressed ga                                    | s; H220 H280                               |                                 |            |
| 110-54-3   | n-Hexane  |  |                                 | < 1 %      |
|            | 203-777-6   | 601-037-00-0                               | 01-2119480412-44                |            |
|            | Flam. Liq. 2, Repr. 2, Skin Irri<br>H361f H315 H336 H373 H304 | t. 2, STOT SE 3, STOT RE 2, Asp.<br>I H411 | Tox. 1, Aquatic Chronic 2; H225 |            |
| 110-82-7   | Cyclohexane   |  |                                 | < 1 %      |
|            | 203-806-2   | 601-017-00-1                               | 01-2119463273-41                |            |
|            | Flam. Liq. 2, Skin Irrit. 2, STC<br>H315 H336 H304 H400 H410  | T SE 3, Asp. Tox. 1, Aquatic Acute         | e 1, Aquatic Chronic 1; H225    |            |

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

| CP00III0 C | • · · · • · · · · · · · · · · · · · · · | 1401010 4114 7 11 =  |           |
|------------|---|--|-----------|
| CAS No     | EC No                                   | Chemical name  | Quantity  |
|            | Specific Cond                           | c. Limits, M-factors and ATE   |           |
| 141-78-6   | 205-500-4                               | Ethyl acetate  | 25 - 50 % |
|            | dermal: LD50                            | ) = > 18000 mg/kg; oral: LD50 = 5620 mg/kg                                   |           |
| 106-97-8   | 203-448-7                               | Butane   | 10 - 25 % |
|            | inhalation: L0                          | C50 = 658 ppm (gases)  |           |
| 110-54-3   | 203-777-6                               | n-Hexane   | < 1 %     |
|            | STOT RE 2; I                            | H373: >= 5 - 100   |           |
| 110-82-7   | 203-806-2                               | Cyclohexane  | < 1 %     |
|            | inhalation: L0                          | C50 = 14 mg/l (vapours); dermal: LD50 = 2000 mg/kg; oral: LD50 = 12705 mg/kg |           |

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures





according to UK REACH Regulation

# **Prema Adhesive Weight Remover**

Revision date: 01.09.2021 Product code: 00623-0017 Page 4 of 12

#### **General information**

Remove contaminated soaked clothing immediately.

Take away from danger area and lay down affected person.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.

#### After contact with skin

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

## After ingestion

Do not induce vomiting.

Rinse mouth.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

## 4.2. Most important symptoms and effects, both acute and delayed

Causes serious eve irritation.

Causes skin irritation.

May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

Attention. Beware, danger of aspiration.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

## Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

# Unsuitable extinguishing media

Full water jet

# 5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

## 5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

#### **Additional information**

Heating will cause pressure rise with risk of bursting.

Cool containers at risk with water spray jet.

Vapours can form an explosive mixture with air.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### **General measures**

Ensure adequate ventilation.

Keep away noninvolved persons.



according to UK REACH Regulation

# **Prema Adhesive Weight Remover**

Revision date: 01.09.2021 Product code: 00623-0017 Page 5 of 12

#### For non-emergency personnel

Do not breathe vapours and aerosols.

Avoid contact with skin, eyes and clothing.

## For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

#### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

## 6.3. Methods and material for containment and cleaning up

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

#### For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

## 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

## Advice on safe handling

Avoid contact with the skin and the eyes.

Use only in thoroughly ventilated areas.

## Advice on protection against fire and explosion

Do not smoke - volatile.

Keep away from open flames, hot surfaces and sources of ignition.

Pay attention to anti-explosion rules.

Do not spray on a naked flame or any other incandescent material.

# 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Protect against direct sun radiation.

Keep container tightly closed.

Use only in well-ventilated areas.

Avoid temperatures above 50°C.

## Hints on joint storage

Incompatible with oxidizing agents.

## **Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

## 7.3. Specific end use(s)

Cleaning agent

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters



according to UK REACH Regulation

# **Prema Adhesive Weight Remover**

Revision date: 01.09.2021 Product code: 00623-0017 Page 6 of 12

# **Exposure limits (EH40)**

| CAS No   | Substance     | ppm | mg/m³ | fibres/ml | Category      | Origin |
|----------|---------------|-----|-------|-----------|---------------|--------|
| 106-97-8 | Butane        | 600 | 1450  |           | TWA (8 h)     | WEL    |
|          |               | 750 | 1810  |           | STEL (15 min) | WEL    |
| 110-82-7 | Cyclohexane   | 100 | 350   |           | TWA (8 h)     | WEL    |
|          |               | 300 | 1050  |           | STEL (15 min) | WEL    |
| 141-78-6 | Ethyl acetate | 200 | 734   |           | TWA (8 h)     | WEL    |
|          |               | 400 | 1468  |           | STEL (15 min) | WEL    |
| 110-54-3 | n-Hexane      | 20  | 72    |           | TWA (8 h)     | WEL    |

# 8.2. Exposure controls

# Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

Do not breath vapours or spray mist.

#### Eye/face protection

Safety goggles with side protection (EN 166).

Eve wash bottle with pure water (EN 15154).

#### Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

# Skin protection

. . . . .

Long sleeved clothing (DIN EN ISO 6530)

# **Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: Colourless
Odour: Fruity

| 1000 111001100 | T | est | met | hod |
|----------------|---|-----|-----|-----|
|----------------|---|-----|-----|-----|

| pH-Value:                                  | n.d. |
|--|------|
| Changes in the physical state              |      |
| Melting point/freezing point:              | n.d. |
| Boiling point or initial boiling point and | n.d. |
| boiling range:                             |      |
| Sublimation point:                         | n.d. |
| Softening point:                           | n.d. |
| Pour point:                                | n.d. |



according to UK REACH Regulation

| Revision date: 01.09.2021                           | Prema Adhesive Weight Remover Product code: 00623-0017 | Dogo 7 of 10        |
|---|--|---------------------|
| Revision date: 01.09.2021                           | Product code: 00623-0017                               | Page 7 of 12        |
| Flash point:  | < 0 °C   |                     |
| Flammability  |  |                     |
| Solid/liquid:                                       | n.a.   |                     |
| Gas:  | n.d.   |                     |
| Explosive properties  The product is considered nor | n-explosive; nevertheless explosive vapour/air mixtu   | re can be generated |
| Lower explosion limits:                             | n.d.   |                     |
| Upper explosion limits:                             | n.d.   |                     |
| Auto-ignition temperature:                          | n.d.   |                     |
| Self-ignition temperature                           |  |                     |
| Solid:  | n.a.   |                     |
| Gas:  | n.d.   |                     |
| Decomposition temperature:                          | n.d.   |                     |
| Oxidizing properties  Not oxidising.                |  |                     |
| Vapour pressure:<br>(at 20 °C)                      | 3000 hPa   |                     |
| Vapour pressure:<br>(at 50 °C)                      | < 10000 hPa  |                     |
| Density (at 20 °C):                                 | 0,658 g/cm³  |                     |
| Bulk density:                                       | n.a.   |                     |
| Water solubility:<br>(at 20 °C)                     | Immiscible   | OECD 116            |
| Solubility in other solvents n.d.                   |  |                     |
| Partition coefficient n-octanol/wat                 | er: n.d.   |                     |
| Viscosity / dynamic:                                | n.d.   |                     |
| Viscosity / kinematic:                              | n.d.   |                     |
| Flow time:  | n.d.   |                     |
| Relative vapour density:                            | n.d.   |                     |
| Evaporation rate:                                   | n.d.   |                     |
| Solvent separation test:                            | n.d.   |                     |
| Solvent content:                                    | n.d.   |                     |
|   |  |                     |

# 9.2. Other information

No data available

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

No decomposition if stored and applied as directed.

## 10.2. Chemical stability

Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

# 10.4. Conditions to avoid

Vapours may form explosive mixture with air.



according to UK REACH Regulation

# **Prema Adhesive Weight Remover**

Revision date: 01.09.2021 Product code: 00623-0017 Page 8 of 12

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Heating will cause pressure rise with risk of bursting.

## 10.5. Incompatible materials

oxidizing agents

## 10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide and carbon dioxide

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in GB CLP Regulation

## **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

LD50/oral/rat: > 5840 mg/kg (OECD 401) LD50/dermal/rat: > 2920 mg/kg (OECD 402)

LC50/inhalation/rat: > 23,3 mg/l/4 h

Hydrocarbons, C6, isoalkanes, < 3% n-hexane

LD50/oral/rat: 16570 mg/kg (OECD 401) LD50/dermal/rat: 3350 mg/kg (OECD 402) LC50/inhalation/rat: 259354 mg/m³/4 h

Ethyl acetate

LD50/oral/rat: 4935 mg/kg LD50/dermal/rat: > 5000 mg/kg LC50/inhalation/rat: 30 mg/l/4 h

## Irritation and corrosivity

Causes serious eve irritation.

Causes skin irritation.

# Sensitising effects

Based on available data, the classification criteria are not met.

# Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

# STOT-single exposure

May cause drowsiness or dizziness. (Ethyl acetate; Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes; Hydrocarbons, C6, isoalkanes, < 3% n-hexane)

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

# **Aspiration hazard**

Based on available data, the classification criteria are not met.

## Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### 11.2. Information on other hazards

# **Endocrine disrupting properties**

No data available

#### Other information

High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.



according to UK REACH Regulation

# **Prema Adhesive Weight Remover**

Revision date: 01.09.2021 Product code: 00623-0017 Page 9 of 12

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

LC50/Oncorhynchus mykiss/96 h = 13,4 mg/kg

NOEC/Oncorhynchus mykiss/28 d = 1,534 mg/l

EC50/Daphnia magna/48 h = 3,0 mg/l

NOEC/Daphnia magna/21 h = 0,17 mg/l

ErC50/Pseudokirchneriela subcapitata/48 h = 20 mg/l

Hydrocarbons, C6, isoalkanes, < 3% n-hexane

LC50/Oncorhynchus mykiss/96 h = 18,27 mg/l

NOEC/Oncorhynchus mykiss/28 d = 4,089 mg/l

EC50/Daphnia magna/48 h = 31,9 mg/l

NOEC/Daphnia magna/21 h = 7,138 mg/l

ErC50/Pseudokirchneriela subcapitata/48 h = 3,034 mg/l

Ethyl acetate

LC50/EC50/EC50 : > 100 mg/l

Cyclohexane

EC50/Daphnia magna/48 h = 0,9 mg/l

IC50/Selenastrum capricornutum/72 h > 4 mg/l

n-Hexane

LC50/Fish/96 h = 1 - 10 mg/kg

EC50/Daphnia magna/48 h = 1 - 10 mg/kg

#### 12.2. Persistence and degradability

No data available

# 12.3. Bioaccumulative potential

No data available

#### 12.4. Mobility in soil

No data available

# 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

#### 12.6. Endocrine disrupting properties

No data available

#### 12.7. Other adverse effects

Hazardous water pollutant.

# **Further information**

Do not flush into surface water or sanitary sewer system.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

# List of Wastes Code - residues/unused products



according to UK REACH Regulation

# **Prema Adhesive Weight Remover**

Revision date: 01.09.2021 Product code: 00623-0017 Page 10 of 12

150111 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers; hazardous waste

#### Contaminated packaging

Offer empty spray cans to an established disposal company.

# **SECTION 14: Transport information**

# Land transport (ADR/RID)

**14.1. UN number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Limited quantity: 1 L / 30 kg
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

**14.1. UN number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Limited quantity: 1 L / 30 kg
Excepted quantity: E0

Marine transport (IMDG)

**14.1. UN number:** UN 1950

14.2. UN proper shipping name: AEROSOLS (Hydrocarbons)

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Marine pollutant:

Limited quantity:

Excepted quantity:

EmS:

Yes

1 L / 30 kg

E0

F-D, S-U



according to UK REACH Regulation

# **Prema Adhesive Weight Remover**

Revision date: 01.09.2021 Product code: 00623-0017 Page 11 of 12

# Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Limited quantity Passenger: 30 kg G Passenger LQ: Y203 Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

# 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

# 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 57

2004/42/EC (VOC): 658 g/l

Information according to 2012/18/EU P3a FLAMMABLE AEROSOLS

(SEVESO III):

# **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

# 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 2,6,7,10,11,12,14,15.



PREMA GmbH

according to UK REACH Regulation

# **Prema Adhesive Weight Remover**

Revision date: 01.09.2021 Product code: 00623-0017 Page 12 of 12

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

## Relevant H and EUH statements (number and full text)

| H220   | Extremely flammable gas.   |
|--------|--|
| H222   | Extremely flammable aerosol.                                       |
| H225   | Highly flammable liquid and vapour.                                |
| H229   | Pressurised container: May burst if heated.                        |
| H280   | Contains gas under pressure; may explode if heated.                |
| H304   | May be fatal if swallowed and enters airways.                      |
| H315   | Causes skin irritation.  |
| H319   | Causes serious eye irritation.                                     |
| H336   | May cause drowsiness or dizziness.                                 |
| H361f  | Suspected of damaging fertility.                                   |
| H373   | May cause damage to organs through prolonged or repeated exposure. |
| H400   | Very toxic to aquatic life.  |
| H410   | Very toxic to aquatic life with long lasting effects.              |
| H411   | Toxic to aquatic life with long lasting effects.                   |
| EUH066 | Repeated exposure may cause skin dryness or cracking.              |
|        |  |

## **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)